

Indicator Type Micrometers SERIES 107

Measurement example



Typical indicator choice

Dial indicator (0.01 mm): **2046AB**

Dial indicator (0.001 mm): **2109AB-10**

ABS Digimatic Indicator (0.01 mm): **543-710B**

ABS Digimatic Indicator (0.0005 mm): **543-700B**

- Designed to mount a dial indicator for direct GO/±NG judgment for mass-produced parts.
- Anvil retracting trigger for quick measurement.

- Various kinds of indicators* are available depending on the measurement type (accuracy required, measuring range, etc.).
- Measuring faces: Carbide tipped
- Anvil stroke: 3 mm

* Only stems of ø8 diameter are supported, but even these may not be supported by some models. Please contact our Customer Support Center or your nearest Mitutoyo sales office for detailed specifications.



SPECIFICATIONS

Metric				
Code No.	Range (mm)	Spindle feed error (μm)	Flatness (μm)	Parallelism (μm)
107-201	0 - 25	3	0.6	2
107-202	25 - 50			
107-203	50 - 75			
107-204	75 - 100			
107-205	100 - 125			3
107-206	125 - 150			
107-207	150 - 175			
107-208	175 - 200			

- Setting standard, 1 pc. (except for measuring range 0 to 25 mm models), Spanner (**301336**), 1 pc.

DIMENSIONS

