

# Micrometer

**ABSOLUTE™**



Oil- and Water Protected  
www.tuv.com ID: 22370448

Applicable models:  
**series 422 Quickmike type**

## Measurement example



## Blade Micrometers

### SERIES 422 — Non-rotating Spindle Type

- The anvil and the spindle have a blade for measuring the groove diameter of shafts, keyways and other hard-to-reach areas.
- Carbide-tipped measuring faces are available.
- Non-rotating spindle type.
- Equipped with Ratchet Stop for constant measuring force.



## SPECIFICATIONS

Metric						
Code No.	Range (mm)	Resolution (mm)	Maximum permissible error $J_{MPE}$ (μm)	Parallelism (μm)	Remark	
Digimatic						
422-230-30	0 - 25	0.001	±3	3	Type A	
422-231-30	25 - 50					
422-232-30	50 - 75					
422-233-30	75 - 100					
422-260-30	0 - 25		±3	3	Type B	
422-261-30	25 - 50					
422-270-30	0 - 25					Type C
422-271-30						

Inch / Metric						
Code No.	Range (in)	Resolution	Maximum permissible error $J_{MPE}$ (in)	Parallelism (in)	Remark	
Digimatic						
422-330-30	0 - 1	0.00005 in/ 0.001 mm	±0.00015	0.00015	Type A	
422-331-30	1 - 2					
422-332-30	2 - 3					
422-333-30	3 - 4					
422-360-30	0 - 1		±0.00015	0.00015	Type B	
422-361-30	1 - 2					
422-370-30	0 - 1					Type C
422-371-30						


Metric Quickmike type					
Code No.	Range (mm)	Resolution (mm)	Maximum permissible error $J_{MPE}$ (μm)	Parallelism (μm)	Remark
Digimatic					
422-411-20	0 - 30	0.001	±3	3	Type A
422-412-20	25 - 55				

Inch / Metric Quickmike type					
Code No.	Range (in)	Resolution	Maximum permissible error $J_{MPE}$ (in)	Parallelism (in)	Remark
Digimatic					
422-421-20	0 - 1.2	0.00005 in/ 0.001 mm	±0.00015	0.00015	Type A
422-422-20	1 - 2.2				

- Power source: SR44 battery (1 pc.), **938882** included as standard (for operational checks)
- Battery life: Approx. 2.4 years under normal use (for **422-2XX, 3XX**)  
Approx. 5 years under normal use (for **422-4XX**)
- Position detection method: Electromagnetic rotary sensor (for **422-2XX, 3XX**)  
Electrostatic capacity absolute sensor (for **422-4XX**)
- Standard accessories: Setting standard, 1 pc. (except for measuring range 0 to 25 mm/0 to 30 mm (0 to 1 in/0 to 1.2 in) models), Spanner (**301336**), 1 pc. (for **422-2XX, 3XX**)

Note 1: For functional details, refer to page 02-7. Please note that these models are not water-proof.  
Note 2: A heat shield is provided with Digimatic models as standard.

## Type and dimensions



## Optional Accessories

Code No.	Type	Description
<b>05CZA662</b>	B	Connection cable (1 m)
<b>05CZA663</b>	B	Connection cable (2 m)
<b>06AFM380B</b>	B	USB Input Tool Direct (2 m)
<b>02AZD790B</b>	B	Connection cable for <b>U-WAVE-T</b> (160 mm)
<b>02AZE140B</b>	B	Connection cable for <b>U-WAVE-T</b> For foot switch
<b>264-622</b>	IP67	<b>U-WAVE-TM*</b>
<b>264-623</b>	Buzzer	<b>U-WAVE-TM*</b>
<b>264-626</b>	IP67	<b>U-WAVE-TMB*</b>
<b>264-627</b>	Buzzer	<b>U-WAVE-TMB*</b>
<b>02AZF310</b>	IP67	Connecting unit for <b>U-WAVE-TM/TMB*</b>

\* Only series 422 (except for Quickmike type) can be attached.