

Measurement example



Optional Accessories

Code No.	Type	Description
264-020	—	USB Input Tool Series USB Keyboard Signal Conversion Type <b>IT-020U</b>
05CZA624	A	Connection cable for <b>IT/DP/MUX</b> (1 m)* <sup>1</sup>
05CZA625	A	Connection cable for <b>IT/DP/MUX</b> (2 m)* <sup>1</sup>
959149	C	Connection cable for <b>IT/DP/MUX</b> (1 m)* <sup>2</sup>
959150	C	Connection cable for <b>IT/DP/MUX</b> (2 m)* <sup>2</sup>
06AFM380A	A	USB Input Tool Direct (2 m)* <sup>1</sup>
06AFM380C	C	USB Input Tool Direct (2 m)* <sup>2</sup>
02AZD730G	IP67	<b>U-WAVE-T</b>
02AZD880G	Buzzer	<b>U-WAVE-T</b>
02AZE200	—	<b>U-WAVE-T</b> mounting bracket
02AZD790A	A	Connection cable for <b>U-WAVE-T</b> (160 mm)* <sup>1</sup>
02AZE140A	A	Connection cable for <b>U-WAVE-T</b> * <sup>1</sup> For foot switch
02AZD790C	C	Connection cable for <b>U-WAVE-T</b> (160 mm)* <sup>2</sup>
02AZE140C	C	Connection cable for <b>U-WAVE-T</b> * <sup>2</sup> For foot switch
264-620	IP67	<b>U-WAVE-TC</b> * <sup>1</sup>
264-621	Buzzer	<b>U-WAVE-TC</b> * <sup>1</sup>
264-624	IP67	<b>U-WAVE-TCB</b> * <sup>1</sup>
264-625	Buzzer	<b>U-WAVE-TCB</b> * <sup>1</sup>
02AZF310	IP67	Connecting unit for <b>U-WAVE-TC/TCB</b> * <sup>1</sup>

\*1 For IP67 models (up to 300 mm)  
\*2 For series 550-2XX and 550-22X.

**ABSOLUTE Digimatic Caliper  
SERIES 550 — with Nib Style Jaws**

ISO13385-1 compliant

- This model can measure both inside and outside dimensions with a specially shaped jaw.
- The digital display can reduce human error by preventing incorrect reading of measurement results. **550-3XX-20** is rated at IP67 and therefore can be reliably used at the manufacturing site.
- Data output function allows integration into statistical process control and measurement systems. (Refer to page 09-3.)
- ID measurement value: displayed value + (a compensation value displayed on the main unit). OFFSET switch allows to input a compensation value so that the measurement value can be read directly (**Code No. 550-301-20, 550-331-20, 550-311-20 and 550-341-20**). Preset function allows to set a desired starting point (**550-331-20 and 550-341-20**).



SPECIFICATIONS

Metric					
Code No.	Range (mm)* <sup>1</sup>	Resolution (mm)	Maximum permissible error (mm)* <sup>2</sup>		Remarks
			EMPE	SMPE	
550-301-20	0 - 200 (10.1 - 210)	0.01	±0.03	±0.03	IP67, with offset
550-331-20	0 - 300 (10.1 - 310)		±0.04	±0.04	IP67, with offset/preset function for easy inside measurement
550-203-10	0 - 450 (20.1 - 470)		±0.05	±0.05	—
550-205-10	0 - 600 (20.1 - 620)		—	—	—
550-207-10	0 - 1000 (20.1 - 1020)		±0.07	±0.07	—

Inch / Metric					
Code No.	Range* <sup>1</sup>	Resolution	Maximum permissible error* <sup>2</sup>		Remarks
			EMPE	SMPE	
550-311-20	0 - 8 in/0 - 200 mm (0.404 - 8.4 in/10.26 - 210.16 mm)	0.0005 in/ 0.01 mm	±0.0015 in/ ±0.03 mm	±0.0015 in/ ±0.03 mm	IP67, with offset
550-341-20	0 - 12 in/0 - 300 mm (0.404 - 12.4 in/10.26 - 310.16 mm)		±0.002 in/ ±0.04 mm	±0.002 in/ ±0.04 mm	IP67, with offset/preset function for easy inside measurement
550-223-10	0 - 18 in/0 - 450 mm (0.504 - 18.5 in/12.8 - 462.7 mm)		±0.002 in/ ±0.05 mm	±0.002 in/ ±0.05 mm	—
550-225-10	0 - 24 in/0 - 600 mm (0.504 - 24.5 in/12.8 - 612.7 mm)		±0.003 in/ ±0.07 mm	±0.003 in/ ±0.07 mm	—
550-227-10	0 - 40 in/0 - 1000 mm (1.004 - 41 in/25.5 - 1025.4 mm)		—	—	—

- Power source: SR44 battery (1 pc.), **938882** included as standard (for operational checks)
- Position detection method: ABSOLUTE electromagnetic induction linear encoder
- Response speed: Unlimited
- \*1 ( ): Inside measurement
- \*2 The Partial Surface Contact Error (EMPE) and Shift Error (SMPE) are terms defined by ISO 13385-1:2019.

DIMENSIONS

Unit: mm

Range (mm)	D	G	S	W	H	t	R
0 - 200 (0 - 8 in)*	60	5 (5.08)*	8	76	16	3	5 (5.08)*
0 - 300 (0 - 12 in)*	75		12	95	20	3.8	
0 - 450 (0 - 18 in)*	100	10 (6.35)*	18	125	25	6	10 (6.35)*
0 - 600 (0 - 24 in)*			24	172	32	8	10 (12.7)*
0 - 1000 (0 - 40 in)*	140	10 (12.7)*	24	172	32	8	10 (12.7)*

\* Inch model