

## ABSOLUTE Digimatic Height Gage SERIES 570 — Standard Model

### Functions

- Zero-setting
- +/- directional measurement
- Data hold
- Data output
- Presetting
- inch/mm reading (inch/mm models)
- Preset value memory
- Origin restoration
- Low battery voltage alert
- Counting value composition error alert

### Standard Accessories

Code No.	Description	Models
900173	Scriber	570-227 570-244
905200	Scriber	570-230 570-248
901338	Scriber clamp box	570-227 570-244
05GZA033	Scriber clamp box	570-230 570-248

### Optional Accessories

Code No.	Type	Description
264-020	—	USB Input Tool Series USB Keyboard Signal Conversion Type IT-020U
905338	F	Connection cable (1 m)
905409	F	Connection cable (2 m)
06AFM380F	F	USB Input Tool Direct (2 m)
02AZD730G	IP67	U-WAVE-T
02AZD880G	Buzzer	U-WAVE-T
02AZE990	—	U-WAVE-T mounting bracket
02AZD790F	F	Connection cable for U-WAVE-T (160 mm)
02AZE140F	F	Connection cable for U-WAVE-T For foot switch

- Simple design is easy to use.
- Scriber is provided as a standard accessory.
- When a dial indicator or dial test indicator is used with **570-227** and **244**, the dedicated holding bar (**953639**, overall length 50 mm) is recommended for use. However, MPE (Maximum permissible error) may be larger because the measurement point is further from the beam.



570-227

### SPECIFICATIONS

Metric						
Code No.	Range (mm)	Resolution (mm)	Fine feed (mm)	Maximum permissible error $E_{MPE}$ (mm)*	Height (mm)	Mass (kg)
570-227	0 - 200	0.01	4	±0.03	355	1.4
570-230	0 - 1000		6	±0.07	1260	16.8
Inch/Metric						
Code No.	Range (in)	Resolution	Fine feed (in)	Maximum permissible error $E_{MPE}$ (in)*	Height (mm)	Mass (kg)
570-244	0 - 8	0.0005 in/0.01 mm	0.16	±0.002	355	1.4
570-248	0 - 40		0.24	±0.003	1260	16.8

- Power source: SR44 battery (1 pc.), **938882** included as standard (for operational checks)
- Battery life: Approx. 5,000 hours under normal use
- \* Maximum permissible error,  $E_{MPE}$  is the term (notation) used in JIS B 7517: 2018, revised based on ISO/TR 14253-6: 2012.

### DIMENSIONS

