



**SERIES 2 — Standard Type, 0.001 mm & 0.005 mm Graduation**

- Standard 0.001 mm and 0.005 mm graduation dial indicators have a bezel with an outside diameter of 57 mm. These indicators provide excellent accuracy and durability.
- The indicator is highly durable thanks to its oil- and water-tight design, quenched hardened stainless-steel, carbide contact point, and a grand gear made of wear- and deformation-resistant material.
- Application of an anti-reflective and hard surface coating improves scale visibility along with scratch and chemical resistance.
- The indicator uses jeweled bearings, providing excellent indication sensitivity and durability.



2109A-10

07  
Indicators

**SPECIFICATIONS**

□ ISO/JIS type

Code No.		Graduation (mm)	Range (range/rev) (mm)	Maximum permissible error (MPE) (µm)						Dial reading	Measuring force (N)
w/lug	Flat-back			Indication error				Hysteresis	Repeat-ability		
				1/10 Rev	1/2 Rev	1 Rev	Measuring range				
<b>2109A-10</b>	<b>2109AB-10</b>	0.001	1 (0.2)	2	3	4	5	2	0.5	0-100-0	1.5 or less
<b>2110A-10</b>	<b>2110AB-10</b>	0.001	1 (0.1)	2	3	4	5	2	0.5	±0-100	1.8 or less
<b>2113A-10</b>	<b>2113AB-10</b>	0.001	2 (0.2)	2	4	5	7	2	0.5	0-100-0	1.5 or less
<b>2118A-10</b>	<b>2118AB-10</b>	0.001	5 (0.2)	3.5	5	6	10	3	1	0-100-100	1.5 or less
<b>2119A-10</b>	<b>2119AB-10</b>	0.001	5 (0.2)	3.5	5	6	10	3	1	0-100-0	1.5 or less
<b>2124A-10</b>	<b>2124AB-10</b>	0.005	5 (0.5)	5	8	9	12	3	3	±0-50	1.5 or less

Note: Completed products inspection is performed in the vertical orientation (contact point downward) and the stated accuracy is guaranteed.

**DIMENSIONS**

ISO/JIS Type

Unit: mm

Code No.	A	B	C	D	E	F	G	H	I	Mass (g)	
										w/lug	Flat-back
<b>2109A-10</b>	47.2	60.5	57	18.1	20	16.9	15.1	52	7.6	148	139
<b>2110A-10</b>	47.2	66.5	57	18.1	20	16.9	21.1	52	7.6	149	140
<b>2113A-10</b>	47.2	61	57	18.1	20	16.9	15.6	52	7.6	148	139
<b>2118A-10</b>	47.2	60.7	57	18.1	20	16.9	15.3	52	7.6	146	137
<b>2119A-10</b>	47.2	60.7	57	18.1	20	16.9	15.3	52	7.6	146	137
<b>2124A-10</b>	47.2	60.7	57	18.1	20	16.9	15.3	52	7.6	146	137

Note: Refer to pages 07-63 to 07-68 for details of contact points.

Dial Indicators