

Holtest

Digimatic Holtest SERIES 468 — Three-point Bore Micrometers

Interchangeable Head Sets



Setting rings are supplied as standard
($\varnothing 125$, $\varnothing 175$) (Packed separately)

468-975

Accessories (optional)

Refer to page 08-4.

| Metric | | | Inch / Metric | | |
|--|-------------|-------------------------------------|----------------|-------------|----------------|
| Set code No. | Range* (mm) | Content of set | Set code No. | Range* (in) | Content of set |
| 468-975 | 100 - 200 | Display unit | 468-980 | 4 - 8 | Display unit |
| | | 100 - 200 mm | | | 4 - 8 in |
| | | Measuring head | | | Measuring head |
| | | 100 - 125 mm | | | 4 - 5 in |
| | | 125 - 150 mm | | | 5 - 6 in |
| | | 150 - 175 mm | | | 6 - 7 in |
| | | 175 - 200 mm | | | 7 - 8 in |
| Setting ring ($\varnothing 125$, $\varnothing 175$) | 1 pc. each | Setting ring (5 in DIA., 7 in DIA.) | 1 pc. each | | |
| Extension rod (150 mm) | 1 pc. | Extension rod (150 mm) | 1 pc. | | |
| Spanner | 2 pcs. | Spanner | 2 pcs. | | |
| Hex wrench | 1 pc. | Hex wrench | 1 pc. | | |
| Phillips screwdriver | 1 pc. | Phillips screwdriver | 1 pc. | | |

* The measurement range cannot be enlarged by measuring heads that are not standard-supplied (the accuracy is not guaranteed).