



140-158

### SPECIFICATIONS

#### Metric

Code No.	Range (mm)	Graduation (mm)	Spindle feed error* (μm)	Micrometer head stroke (mm)	Extension pipes		Main unit (mm)
					Qty	Size (mm)	
140-157	1000 - 2000	0.01	6	50	5	50, 100 (2 pcs.), 200, 500	1000 - 1050
140-158	1000 - 3000				6	50, 100 (2 pcs.), 200, 500, 1000	
140-159	1000 - 4000				7	50, 100 (2 pcs.), 200, 500, 1000 (2 pcs.)	
140-160	1000 - 5000				8	50, 100 (2 pcs.), 200, 500, 1000 (3 pcs.)	

#### Inch

Code No.	Range (in)	Graduation (in)	Spindle feed error* (in)	Micrometer head stroke (in)	Extension pipes		Main unit (in)
					Qty	Size (in)	
140-161	40 - 80	0.001	0.0003	2	5	2, 4 (2 pcs.), 8, 20	40 - 42
140-162	40 - 120				6	2, 4 (2 pcs.), 8, 20, 40	
140-163	40 - 160				7	2, 4 (2 pcs.), 8, 20, 40 (2 pcs.)	
140-164	40 - 200				8	2, 4 (2 pcs.), 8, 20, 40 (3 pcs.)	

\* "Spindle feed error" refers to the difference between the maximum and minimum indication error values within the measuring range of the micrometer head

### DIMENSIONS

